

Flexo-Folder Gluing

Innovative & cost effective solutions!

HAECO

■ A Complete System with the DURO Glue Station



HAECO's Flexo-Folder Gluing System ships as a complete, pre-wired, ready-to-run system! Installation has been simplified by pre-wiring and color coding all controls and cables – giving you the option to install yourself. The new DURO Glue Station introduces many new features to keep standard operations fast and easy while reducing maintenance requirements. This Flexo-Folder Gluing System is not only one of the most robust systems on the market but is also one of the easiest to setup and operate.

Special Features

➤ Built-in Water Purge

Purging an applicator head is faster and easier than ever – and you don't even have to remove the head! Simply turn the supply valve from glue to water and press the valve button to purge glue out from the valve down. When you're ready to run again simply turn the valve back to glue and purge glue. (Requires a regulated water source)

➤ Durable Quality

The DURO Glue Station is now one of the strongest glue stations on the market. The entire system was designed to run large product and provide a long service life even for the most abusive environments.

➤ Jumbo Box Features

Now you can quickly accommodate jumbo box runs. This system is durable enough to handle the largest of boxes and allows operators to quickly add an additional glue station providing up to a 4 inch glue stripe – all you need to do is slide it on and plug it in!

➤ Pre-wired and Easy to Install

Installation has been simplified allowing you to install yourself. Controls are pre-wired with corresponding color coded cables. Once you have the hardware mounted simply match up the colors and plug it in. (200 Volt configuration requires hard-wire power)

➤ Fast Top-Down to Bottom-Up Change

Changing over from top-down to bottom-up gluing is now as simple as sliding the top bracket onto the lower post and the lower bracket on the upper post. There is no need to unhook any fittings and making this change can be completed in less than 30 seconds.

➤ Easy Set Random Length Controls

Never measure tabs again! Simply set the leading and trailing gap and that's it – the controller will automatically adjust for varying tab lengths so there is no further setup needed between different tab lengths. 4th panel gluing is available and requires different controls.



